

Recommended Servos for PST Reaction ARF

JR SERVOS						ELEVATOR	AILERON (2)	FLAP (2)	RUDDER	STERING	VALVES (2)	SPEED BRAKE
SERVO	TYPE	TORQUE 4.8V/6.0V (oz.-inches)	SPEED 4.8V/6.0V (60°/second)	WEIGHT (ounces)	DIMENSIONS (inches)							
537	Analog	40/49	.25/.19	1.58	1.32 x .73 x 1.52						X	
4131	Analog	90/105	.23/.20	1.5	1.32 x .73 x 1.52			X		X	X	X
4721	Analog	119/140	.22/.19	1.72	1.32 x .73 x 1.52			X		X		X
DS8231	Digital	88/113	.22/.19	1.73	1.36 x .75 x 1.54		X	X	X			
DS8411	Digital	155/188	.18/.15	2.03	1.36 x .75 x 1.54	X	X	X				
DS8417	Digital	82/98	.10/.08	2.03	1.36 x .75 x 1.54		X	X	X			

FUTABA SERVOS						ELEVATOR	AILERON (2)	FLAP (2)	RUDDER	STERING	VALVES (2)	SPEED BRAKE
SERVO	TYPE	TORQUE 4.8V/6.0V (oz.-inches)	SPEED 4.8V/6.0V (60°/second)	WEIGHT (ounces)	DIMENSIONS (inches)							
S3004	Analog	44/57	.23/.19	1.3	1.4 x 0.8 x 1.6						X	
S9402	Analog	89/111	.13/.10	1.9	1.5 x 0.8 x 1.6			X		X	X	X
S9350	Digital	111/139	.15/.12	1.4	1.5 x 0.8 x 1.6		X	X	X			
S9351	Digital	152/192	.16/.13	2.15	1.57 x 0.79 x 1.44	X	X	X				
S9156	Digital	272/340	.20/.17	2.22	1.57 x 0.79 x 1.44	X	X	X				

HITEC SERVOS						ELEVATOR	AILERON (2)	FLAP (2)	RUDDER	STERING	VALVES (2)	SPEED BRAKE
SERVO	TYPE	TORQUE 4.8V/6.0V (oz.-inches)	SPEED 4.8V/6.0V (60°/second)	WEIGHT (ounces)	DIMENSIONS (inches)							
HS-625MG	Analog	76/94	.18/.13	1.94	1.59 x 0.77 x 1.48						X	
HS-645MG	Analog	107/133	.24/.20	1.94	1.59 x 0.77 x 1.48			X		X	X	X
HS-965MG	Analog	119/144	.13/.10	2.18	1.55 x 0.78 x 1.48			X		X		X
HS-985MG	Analog	144/172	.16/.13	2.18	1.55 x 0.78 x 1.48			X		X		X
HS-5625MG	Digital	110/131	.17/.14	2.10	1.59 x 0.77 x 1.48		X	X	X			
HS-5645MG	Digital	143/168	.23/.18	2.10	1.59 x 0.77 x 1.48	X		X	X			
HS-5945MG	Digital	153/181	.16/.13	1.97	1.55 x 0.78 x 1.48	X	X	X	X			
HS-5965MG	Digital	105/134	.13/.10	2.18	1.57 x 0.78 x 1.45		X	X				
HS-5985MG	Digital	144/172	.16/.13	2.18	1.55 x 0.78 x 1.48	X	X	X				